



Material Safety Data Sheet

IRON STA II C

HEALTH	*	1
FLAMMABILITY		1
PHYSICAL HAZARD		0
PERSONAL PROTECTION		

1. Product and Company Identification

Material name	IRON STA II C
Patent Number	Not available
Version No.	3
CAS #	Mixture
Product use	Iron Control Agent
Manufacturer information	Clearwater International L.L.C. 100 Leetsdale Industrial Drive Leetsdale, PA 15056 US CHEMTREC 1-800-424-9300/703-527-3887
Emergency	CHEMTREC 1-800-424-9300/703-527-3887
Supplier information	Universal Well Services, Inc. 18360 Technology Drive Meadville, PA 16335 US

2. Hazards Identification

Emergency overview	Prolonged exposure may cause chronic effects. This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Components of the product may be absorbed into the body by inhalation, ingestion and through the skin.
OSHA regulatory status	This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).
Potential health effects	
Eyes	Do not get this material in contact with eyes.
Skin	Do not get this material in contact with skin.
Inhalation	Prolonged inhalation may be harmful. Do not breathe dust/fume/gas/mist/vapors/spray.
Ingestion	May cause delayed lung damage. Do not ingest. Components of the product may be absorbed into the body by ingestion.
Target organs	Central nervous system. Eyes. Lungs. Respiratory system. Skin.
Chronic effects	Shortness of breath. May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion, and blurred vision) and/or damage. May cause delayed lung damage.
Signs and symptoms	Discomfort in the chest. Shortness of breath. Narcosis. Decrease in motor functions. Behavioral changes. Cough.
Potential environmental effects	May cause long-term adverse effects in the environment.





3. Composition / Information on Ingredients

Components	CAS #	Percent
Ethylene Glycol	107-21-1	10 - 30

4. First Aid Measures

First aid procedures

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation develops or persists.

Skin contact

Wash off with soap and water. Get medical attention if irritation develops or persists.

Inhalation

If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention immediately.

Ingestion

If swallowed, seek medical advice immediately and show this container or label. Do not induce vomiting without medical advice.

Notes to physician

Symptoms may be delayed.

General advice

Call a physician if symptoms develop or persist. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire Fighting Measures

Flammable properties

Combustible by OSHA criteria.

Extinguishing media**Suitable extinguishing media**

Dry chemical, CO₂, water spray or regular foam.

Unsuitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

Protection of firefighters**Protective equipment and precautions for firefighters**

Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions. ALWAYS stay away from tanks engulfed in flame. Withdraw immediately in case of rising sound from venting safety devices or any discoloration of tanks due to fire. Move containers from fire area if you can do it without risk. Do not scatter spilled material with high pressure water streams. Use water spray to cool unopened containers. Cool containers with flooding quantities of water until well after fire is out.

6. Accidental Release Measures

Personal precautions

Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering. Keep unnecessary personnel away. Stay upwind. Keep out of low areas.

Methods for containment

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Prevent entry into waterways, sewers, basements or confined areas.



**Methods for cleaning up**

Should not be released into the environment.

Large Spills: Dike far ahead of liquid spill for later disposal. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. After removal flush contaminated area thoroughly with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean contaminated surface thoroughly.

Never return spills in original containers for re-use.

7. Handling and Storage**Handling**

Use only with adequate ventilation. Avoid release to the environment. Wash thoroughly after handling. Avoid prolonged exposure.

Storage

Store in a closed container away from incompatible materials. Store in accordance with local/regional/national/international regulation.

8. Exposure Controls / Personal Protection**Exposure limits****ACGIH****Components****CAS #****TWA****STEL****Ceiling**

Ethylene Glycol

107-21-1

Not established

Not established

100 mg/m³**Engineering controls**

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment**Eye / face protection**

Wear chemical goggles.

Skin protection

Wear chemical protective equipment that is specifically recommended by the manufacturer. It may provide little or no thermal protection. Protective gloves. Impervious gloves.

Respiratory protection

Wear positive pressure self-contained breathing apparatus (SCBA). When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

General hygiene considerations

When using do not eat or drink. Keep away from food and drink. Handle in accordance with good industrial hygiene and safety practice.

9. Physical & Chemical Properties**Appearance**

Liquid.

Color

clear, light yellow light yellow light yellow light yellow light yellow light yellow

Odor

ammoniacal

Odor threshold

Not available

Physical state

Liquid.

Form

Liquid.

pH

3.5 - 5

Melting point

28.4 °F (-2.09 °C) estimated

Freezing point

Not available





Boiling point	244.4 °F (118 °C) estimated
Flash point	200 °F (93.3 °C)
Evaporation rate	Not available
Flammability	Not available.
Flammability limits in air, upper, % by volume	Not available
Flammability limits in air, lower, % by volume	Not available
Vapor pressure	Not available
Vapor density	Not available
Specific gravity	1.2 - 1.24
Relative density	1.2199 g/cm ³ estimated
Solubility (water)	Not available
Partition coefficient (n-octanol/water)	Not available
Auto-ignition temperature	748.4 °F (398 °C) estimated
Decomposition temperature	Not available
VOC	8.7 % estimated

10. Chemical Stability & Reactivity Information

Chemical stability	Stable at normal conditions.
Conditions to avoid	Heat, flames and sparks.
Incompatible materials	Amines. Isocyanates. Strong oxidizing agents. Strong acids. Caustics.

11. Toxicological Information

Acute effects	Acute LD50: 46000 mg/kg estimated, Rat, Oral
Component analysis - LD50	
Toxicology Data - Selected LD50s and LC50s	
Ethylene Glycol	107-21-1 Oral LD50 Rat: 4000 mg/kg; Dermal LD50 Rabbit: 9530 µL/kg
Sensitization	Not expected to be hazardous by OSHA criteria.
Chronic effects	Hazardous by OSHA criteria. Repeated absorption may cause disorder of central nervous system, liver, kidneys and blood. Prolonged or repeated exposure may cause lung injury. Prolonged exposure may cause chronic effects.
Carcinogenicity	Not expected to be hazardous by OSHA criteria.
ACGIH - Threshold Limits Values - Carcinogens	
Ethylene Glycol	107-21-1 A4 - Not Classifiable as a Human Carcinogen
Neurological effects	Hazardous by OSHA criteria.
Further information	Symptoms may be delayed.





12. Ecological Information

Ecotoxicity

Components of this product have been identified as having potential environmental concerns.

Ecotoxicity - Freshwater Algae Data

Ethylene Glycol 107-21-1 96 Hr EC50 *Selenastrum capricornutum*: 6500-1300 mg/L

Ecotoxicity - Freshwater Fish Species Data

Ethylene Glycol 107-21-1 96 Hr LC50 *Oncorhynchus mykiss*: 41000 mg/L; 96 Hr LC50 *Lepomis macrochirus*: 27500 mg/L; 96 Hr LC50 *Oncorhynchus mykiss*: 40761 mg/L [static]; 96 Hr LC50 *Pimephales promelas*: 49000 mg/L [static]; 96 Hr LC50 *Poecilia reticulata*: 16000 mg/L [static]

Ecotoxicity - Microtox Data

Ethylene Glycol 107-21-1 30 min EC50 *Photobacterium phosphoreum*: 620.0 mg/L; 30 min EC50 *Photobacterium phosphoreum*: 620 mg/L; 16 Hr EC50 *Pseudomonas putida*: 10000 mg/L

Ecotoxicity - Water Flea Data

Ethylene Glycol 107-21-1 48 Hr EC50 water flea: 46300 mg/L

Environmental effects

Ecotoxicity - Freshwater Algae Data

Ethylene Glycol 107-21-1 96 Hr EC50 *Selenastrum capricornutum*: 6500-1300 mg/L

Ecotoxicity - Freshwater Fish Species Data

Ethylene Glycol 107-21-1 96 Hr LC50 *Oncorhynchus mykiss*: 41000 mg/L; 96 Hr LC50 *Lepomis macrochirus*: 27500 mg/L; 96 Hr LC50 *Oncorhynchus mykiss*: 40761 mg/L [static]; 96 Hr LC50 *Pimephales promelas*: 49000 mg/L [static]; 96 Hr LC50 *Poecilia reticulata*: 16000 mg/L [static]

Ecotoxicity - Microtox Data

Ethylene Glycol 107-21-1 30 min EC50 *Photobacterium phosphoreum*: 620.0 mg/L; 30 min EC50 *Photobacterium phosphoreum*: 620 mg/L; 16 Hr EC50 *Pseudomonas putida*: 10000 mg/L

Ecotoxicity - Water Flea Data

Ethylene Glycol 107-21-1 48 Hr EC50 water flea: 46300 mg/L

13. Disposal Considerations

Disposal instructions

Do not allow this material to drain into sewers/water supplies. This product, in its present state, when discarded or disposed of, is not a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste. Dispose in accordance with all applicable regulations.

14. Transport Information

Department of Transportation (DOT) Requirements

Not regulated as dangerous goods.

Canadian Transportation of Dangerous Goods (TDG) Requirements

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.





15. Regulatory Information

Labelling

Contains Ethylene Glycol

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

Ethylene Glycol 107-21-1 1.0 % de minimis concentration

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous chemical Yes

CERCLA (Superfund) reportable quantity

Ethylene Glycol: 5000.0000

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories
Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

Section 302 extremely hazardous substance No

Section 311 hazardous chemical Yes

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of New and Existing Chemicals (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

International regulations

Canada - WHMIS - Ingredient Disclosure List

Ethylene Glycol 107-21-1 1 %



**State regulations**

This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

U.S. - Massachusetts - Right To Know List

Ethylene Glycol 107-21-1 Present

U.S. - Minnesota - Hazardous Substance List

Ethylene Glycol 107-21-1 Present (particulate and vapor)

U.S. - New Jersey - Right to Know Hazardous Substance List

Ethylene Glycol 107-21-1 sn 0878

U.S. - Pennsylvania - RTK (Right to Know) List

Ethylene Glycol 107-21-1 Environmental hazard

U.S. - Rhode Island - Hazardous Substance List

Ethylene Glycol 107-21-1 Toxic; Flammable

U.S. - Texas - Effects Screening Levels - Long Term

Ethylene Glycol 107-21-1 10 ppb ESL (46% Ethylene glycol); 26 µg/m³ ESL (46% Ethylene glycol)

U.S. - Texas - Effects Screening Levels - Short Term

Ethylene Glycol 107-21-1 100 ppb ESL (46% ethylene glycol); 260 µg/m³ ESL (46% ethylene glycol)

16. Other Information**HMIS® ratings**

Health: 1*
Flammability: 1
Physical hazard: 0

NFPA ratings

Health: 1
Flammability: 1
Instability: 0

Prepared by

Amanda L. Ruston
4420 South Flores Road
Elmendorf, Texas 78112
210-626-0850

Disclaimer

THIS PRODUCT'S HEALTH AND SAFETY INFORMATION IS PROVIDED TO ASSIST OUR CUSTOMERS IN ASSESSING COMPLIANCE WITH HEALTH, SAFETY AND ENVIRONMENTAL REGULATIONS. THE INFORMATION CONTAINED HEREIN IS BASED ON DATA AVAILABLE TO US, AND IS BELIEVED TO BE ACCURATE, ALTHOUGH NO GUARANTEE OR WARRANTY IS PROVIDED OR IMPLIED BY THE COMPANY IN THIS RESPECT. SINCE THE USE OF THIS PRODUCT IS WITHIN THE EXCLUSIVE CONTROL OF THE USER, IT IS THE USER'S RESPONSIBILITY TO DETERMINE THE CONDITIONS OF SAFE USE. SUCH CONDITIONS MUST COMPLY WITH ALL GOVERNMENTAL REGULATIONS.

MSDS sections updated

Product and Company Identification: Product and Company Identification

